

QC- Series Micropipette



Main Features

- Half Autoclavable Micropipette/Full Autoclavable Micropipette
- Light weight, ergonomic design.
- Digital display clearly reads volume setting.
- Wide measurement rang, 0.1ul to 10000ul.
- With new material, it can be fully autoclavable.
- Ceramic piston, high corrosion resistance.
- PTFE sealing ring, more convenient to use.

Technical Specifications:

Model	Volume Range	Testing Volume (µl)	Inaccuracy	Imprecision	Increment (µl)	Tip Volume
QC-10P	0.5 - 10 µl	10	±1.00%	±1.00%	0.1 µl	20 µl
		5	±1.50%	±1.50%		
		1	±2.50%	±2.50%		
QC-20P	2 - 20 µl	20	±0.90%	±0.40%	0.5 µl	200 µl
		10	±1.20%	±1.00%		
		2	±3.00%	±2.00%		
QC-50P	5 - 50 µl	50	±0.60%	±0.30%	0.5 µl	200 µl
		25	±0.90%	±0.60%		
		5	±2.00%	±2.00%		
QC-100P	10 - 100 µl	100	±0.60%	±0.15%	1 µl	200 µl
		50	±0.90%	±0.40%		
		10	±2.00%	±0.10%		
QC-200P	20 - 200 µl	200	±0.60%	±0.15%	1 µl	200 µl
		100	±0.80%	±0.30%		
		20	±3.00%	±1.00%		
QC-1000P	100 - 1000 µl	1000	±0.60%	±0.20%	5 µl	1000 µl
		500	±0.70%	±0.25%		
		100	±1.50%	±0.70%		
QC-5000P	1000 - 5000 µl	5000	±0.50%	±0.15%	50 µl	5000 µl
		2500	±0.60%	±0.30%		
		1000	±0.70%	±0.30%		
QC-10000P	2000 - 10000 µl	10ml	±0.60%	±0.20%	0.1ml	10ml
		5ml	±1.20%	±0.30%		
		2ml	±1.50%	±0.40%		